PPC Series

PPC-200W



Washdown Portable Portion Control Scale

With over/under checkweighing, high accuracy, portability and washdown capability the PPC-200W is perfectly suited for use in the poultry, seafood, meat processing, and food service industries. A very affordable washdown scale with exceptional quality and features.

Features

- Washdown
- Over/Under Indicator
- Large Removable Stainless Steel Platform
- Accurate 2000 Divisions
- Large LCD Display

- Battery Operation
- · Adjustable Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Two (2) Year Warranty





Reliability you can trust



Features

- Washdown IP65
- Over/Under Indicator
- Large Removable Stainless Steel Platform
- Accurate 2000 Divisions
- Large LCD Display
- · Battery Operation
- Adjustable Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Legal for Trade
- Two (2) Year Warranty

Options

S

0

S

0

- RS-232C Serial Communications
- AC Adaptor (not washdown with adaptor installed)

Specifications

	Capacity and Divisions
PPC-200W	4 lb x 0.002 lb 10 lb x 0.005 lb 20 lb x 0.01 lb 40 lb x 0.02 lb 2 kg x 0.001 kg 4 kg x 0.002 kg 10 kg x 0.005 kg 20 kg x 0.01 kg
PPC-200WC	80 oz x 0.05 oz 2 kg x 0.001 kg 4 kg x 0.002 kg 320 oz x 0.2 oz 20 kg x 0.001 kg 800 oz x 0.5 oz 20 kg x 0.001 kg
PPC-200WZ	5 lb x 0.05 oz* 10 lb x 0.1 oz* 20 lb x 0.2 oz* 50 lb x 0.5 oz* 2 kg x 0.001 kg 4 kg x 0.002 kg 10 kg x 0.005 kg 20 kg x 0.01 kg
	*lb-oz - not legal for trade
Accuracy Class	Class III, 2000 divisions
Certificate of Conformance #	98-125A4
Weighing System	Strain gauge load cell
Platform	9" x 9" stainless steel, removable (230 x 230 mm)
Display	LCD: 5 digits plus annunciators Character size: 0.9" x 0.5"
Housing Material	ABS Plastic
Power	6 "D" batteries, optional AC adaptor
Operating Temp	$14^{\rm o}{\rm F}\sim 104^{\rm o}{\rm F}$ (- $10^{\rm o}{\rm C}\sim 40^{\rm o}{\rm C}$)
Battery Life	1000 hours of continuous use
Accuracy Class Certificate of Conformance # Weighing System Platform Display Housing Material Power Operating Temp	2 kg x 0.001 kg 4 kg x 0.002 kg 10 kg x 0.005 kg 20 kg x 0.01 kg *lb-oz - not legal for trade Class III, 2000 divisions 98-125A4 Strain gauge load cell 9" x 9" stainless steel, removable (230 x 230 mm) LCD: 5 digits plus annunciators Character size: 0.9" x 0.5" ABS Plastic 6 "D" batteries, optional AC adaptor 14° F ~ 104° F (-10° C ~ 40° C)





Distributed By:
Pizza Equipment Professionals
Phone: (800) 655-1821
Fax: (209) 824-4684
www.PizzaEquipmentPros.com

info@pizzaequipmentpros.com

